

## About LaHabra

Since 1926 – LaHabra has become the brand you can depend on for quality stucco & EIFS products. Today, LaHabra continues to set new standards for product quality, consistency, reliability and service. LaHabra is a stucco & EIFS industry leader in North America. As a pillar in the Facade industry LaHabra has been instrumental in contributing to the advancement of stucco & EIFS and has developed many technological breakthroughs that are still in use today. LaHabra EIF Systems meet 2009 IBC and IRC Building Code requirements.

## Local Material from a Local Distributor

Parex USA has 9 manufacturing and distribution locations throughout the United States. National coverage provides the best opportunity to source materials locally, reducing time and shipping costs while also contributing toward LEED points.

These locally produced materials are serviced by local distributors who understand the market and can provide the level of service that one would expect from the leading stucco provider.

CEMENT STUCCO FINISHES.....	04
ACRYLIC FINISHES.....	04
ELASTOMERIC FINISHES.....	05
COATINGS, PRIMERS & SEALERS.....	05
STUCCO BASECOATS.....	07
EIFS ADHESIVES & BASECOATS.....	08
BONDING AGENTS & ADMIXTURES.....	09
MESH.....	09
WEATHERTECH.....	10
WATERMASTER COMPONENTS.....	11




CEMENT STUCCO FINISHES		Size	Pack	Coverage (ft <sup>2</sup> )
	<p><b>Exterior Stucco (Base 100 &amp; 200 &amp; Premix)</b></p> <p>LaHabra Exterior Stucco Color Coat provides a lasting, durable color finish over LaHabra Fiber-47 Fastwall Scratch &amp; Brown, LaHabra Fastwall Stucco Base, portland cement plaster "brown coat" and Parex USA Stucco Level Coat. It is integrally colored with fade-resistant pigments, and is economical with low maintenance. Available in premix or tint Base 100 and 200 and 16/20 and 20/30 aggregates for use with LaHabra Color Packs.</p>	90 lbs	30/pallet	Float Finish: 135-180 Light Spanish Texture: 90-135 Machine Dash: 72-108
	<p><b>Santa Barbara Mission Finish</b></p> <p>LaHabra Santa Barbara Mission Finish provides a lasting, durable smooth stucco finish over LaHabra Fiber-47 Fastwall Scratch &amp; Brown, LaHabra Fastwall Stucco Base, exterior plaster "brown coat" and Parex USA Stucco Level Coat. It is integrally colored with fade-resistant pigments, and is economical with low maintenance. Available in premix or tint Base 100 and 200 for use with LaHabra Color Packs.</p>	90 lbs	30/pallet	90-135
	<p><b>Color Pack</b></p> <p>LaHabra Color Packs are specifically designed for use with LaHabra Exterior Color Coat. Available in 30 Standard colors and 12 Lifestyle colors. Special colors are available upon request.</p>	16 oz	15/case	NA
	<p><b>NTS Exterior Stucco (Base 100 &amp; 200)</b></p> <p>NTS Exterior Color Coat is the next leap in stucco technology. NTS provides a lasting, durable color finish that can be applied over LaHabra FastWall Fiber-47 Scratch &amp; Brown, LaHabra Fastwall Stucco Base, portland cement plaster "brown coat" and Parex USA Stucco Level Coat by hand or machine application. Available in premix or tint Base 100 and 200 and 16/20 and 20/30 aggregates for use with LaHabra Color Packs.</p>	90 lbs	30/pallet	Float Finish: 90-135 Light Spanish Texture: 90-135 Machine Dash: 72-90
ACRYLIC FINISHES				
	<p><b>Perma-Flex</b></p> <p>A 100% acrylic-based textured finish for stucco only. Made with Dirt Pick-Up Resistance (DPR) meaning the surface of the finish hardens and does not soften again under heat. The non-tacky surface provides high resistance to accumulation of dirt, mold and pollutants. The finish is integrally colored with high quality pigments. Available in four textures: Fine, Smooth, Swirl and Coarse.</p>	5 gal	36/pallet	Fine: 150-165 Coarse: 110-125 Swirl: 120-135 Smooth: 280-300
	<p><b>Perma-Finish EIFS &amp; Stucco Finish</b></p> <p>A 100% acrylic-based textured finish. Made with Dirt Pick-Up Resistance (DPR) meaning the surface of the finish hardens and does not soften again under heat. The non-tacky surface provides high resistance to accumulation of dirt, mold and pollutants. The finish is integrally colored with high quality pigments. Available in four textures: Fine, Smooth, Swirl and Coarse</p>	5 gal	36/pallet	Fine: 150-165 Coarse: 110-125 Swirl: 120-135 Smooth: 280-300
	<p><b>LaHabra Color Bottles</b></p> <p>LaHabra Color Bottles are specifically designed for use with LaHabra Acrylic and Elastomeric Finishes. Available in 30 Standard colors and 12 Lifestyle colors. Special colors are available upon request.</p>	4 oz	24/case	NA

ACRYLIC FINISHES (continued)	Size	Pack	Coverage (ft <sup>2</sup> )
 <p><b>Parex USA Color Bottles</b> Parex USA Color Bottles are specifically designed for use with Parex USA Acrylic and Elastomeric Finishes. Available in 75 standard colors. Special colors are available upon request.</p>	4 oz	24/case	NA
 <p><b>Parex USA Dry-Tex</b> A 100% dry acrylic-based textured finish. Mix on-site with water and pigment. VOC free and freeze thaw stable Dry-Tex is made with Dirt Pick-Up Resistance (DPR) meaning the surface of the finish hardens and does not soften again under heat. The non-tacky surface provides high resistance to accumulation of dirt, mold and pollutants. Available in two textures: Sand Coarse and Sand Fine</p>	40 lbs	56/pallet	Sand Fine: 150-165 Sand Coarse: 110-125
ELASTOMERIC FINISHES			
 <p><b>Perma-Elastic</b> A 100% acrylic-based elastomeric textured finish. Made with DPR (Dirt Pick-up Resistance) chemistry. Perma-Elastic is highly flexible and can bridge pre-existing or existing hairline cracks. Integrally colored with high quality pigments. Available in three textures: Fine, Coarse and Swirl.</p>	5 gal	36/pallet	Fine: 150-165 Coarse: 120-135 Swirl: 120-135
COATINGS, PRIMERS & SEALERS			
 <p><b>Fog Coat</b> Fog Coat provides cost-effective, durable and long-lasting colored coating for existing stucco. It is easy to apply and specifically designed to refresh the color of stucco. A decorative coating for portland cement based stucco walls and ceilings.</p>	25 lbs	56/pallet	800-1000
 <p><b>Parex USA Allegro II Base</b> Allegro II Cement Coating provides a cost-effective, durable and long-lasting colored coating that can be applied to portland cement surfaces such as: Stucco, Paint grade stucco, Concrete block/Concrete masonry unit (CMU) and Precast concrete.</p>	12 lbs	120/pallet	320-480
 <p><b>Parex USA Allegro II Color Bottles</b> Allegro Color Bottles are specifically designed for use with Parex USA Allegro II Base. Available in 30 Standard colors and 12 Lifestyle colors. Special colors are available upon request.</p>	4-8 oz	each	NA
 <p><b>Parex USA DPR Coating</b> A 100% acrylic-based non-textured coating. Made with DPR (Dirt Pick-up Resistance) chemistry. The non-tacky surface provides high resistance to accumulation of dirt, mold and pollutants. Excellent hiding power as well as flexibility and drying characteristics. The surface of the coating hardens and does not soften under heat. Integrally colored with high quality pigments.</p>	5 gal	36/pallet	1000-1200

COATINGS, PRIMERS & SEALERS (continued)		Size	Pack	Coverage (ft <sup>2</sup> )
	<p><b>Parex USA Elastomeric Coating</b></p> <p>A 100% acrylic Elastomeric non-textured coating. Highly flexible: can bridge existing hairline cracks. DPR (Dirt Pick-up Resistance): The non-tacky surface provides high resistance to accumulation of dirt, mold, and pollutants. It provides excellent hiding power as well as flexibility and drying characteristics. The surface of the coating hardens and does not soften under heat. Integrally colored with high quality pigments.</p>	5 gal	36/pallet	<p>One coat over porous surfaces: 125-180</p> <p>One coat over smooth/filled surface: 350-400</p>
	<p><b>Perma Primer</b></p> <p>A 100% acrylic-based primer. Reduces the chance of efflorescence which may result from the cement content of various bases. Enhances the appearance and uniformity of the finish. Water-vapor permeable. Does not create a vapor retarder. Improves acrylic and elastomeric finish coverage.</p>	5 gal	36/pallet	1600-2000
	<p><b>Parex USA Quik Cure</b></p> <p>Water-based acrylic curing membrane formulated to provide excellent performance in the water retention section of ASTM C 309. Provides a curing membrane over cementitious surfaces allowing acrylic finishes to be applied quickly, while protecting against delamination and efflorescence. Provides a sound, sealed substrate for a uniform finish over either stucco or concrete.</p>	5 gal	36/pallet	900-1200
	<p><b>Parex USA PrimeShield</b></p> <p>A 100 percent acrylic-based primer that improves the mechanical bond of the finish to the stucco substrate. PrimeShield reduces the chance of efflorescence which may result from the cement content of various bases. It also enhances the appearance and uniformity of the finish. The product is water-vapor permeable and does not create a vapor retarder.</p>	5 gal	36/pallet	900-1200
	<p><b>Parex USA Pro-Tect</b></p> <p>Pro-Tect is a clear water repellent used to protect stucco, masonry and mature concrete from water, enhancing the beauty of cementitious stucco, masonry and mature concrete by improving stain resistance. Pro-Tect maintains the beauty of stucco by reducing susceptibility to freeze-thaw damage, efflorescence and biological growth. Available in both one and five gallons.</p>	5 gal	36/pallet	625-750
		1 gal	6/case	125-150
	<p><b>Parex USA 600 Clear Sealer</b></p> <p>A 100% acrylic transparent coating. Contains EPA-registered mildewcide and algicide. Dirt resistant. The coating hardens and does not soften under solar heating. The non-tacky surface provides high resistance to accumulation of dirt and pollutants. Water vapor permeable.</p>	5 gal	36/pallet	160-200
	<p><b>Parex USA 610 Matte Sealer</b></p> <p>A 100% acrylic transparent coating. Developed with a special matte agent to reduce sheen and contains EPA-registered mildewcide and algicide. Dirt resistant. The coating hardens and does not soften under solar heating. The non-tacky surface provides high resistance to accumulation of dirt and pollutants. Water vapor permeable.</p>	5 gal	36/pallet	160-200







STUCCO BASECOATS		Size	Pack	Coverage (ft <sup>2</sup> )
	<p><b>Fastwall Stucco Base Concentrate</b></p> <p>A factory controlled high-quality blend of portland cement, lime, fibers and proprietary additives that conforms to ASTM C926. ASTM C897 or ASTM C144 sand is added at the job site. Can be installed up to 1/2 in. (12.7mm) in one application.</p>	80 lbs	35/pallet	At 3/8": 75-90 At 1/2": 60-72
	<p><b>Fastwall Stucco Base Sanded</b></p> <p>A factory controlled high-quality blend of portland cement, lime, fibers, proprietary additives and ASTM C144 sand that conforms to ASTM C926. Factory-blended mix that requires only the addition of water. Can be installed up to 1/2 in. (12.7mm) in one application.</p>	80 lbs	35/pallet	At 3/8": 20-25 At 1/2": 15-19
	<p><b>Fiber 47 Fastwall Scratch &amp; Brown Concentrate</b></p> <p>A factory controlled high-quality blend of portland cement, lime, fibers and proprietary additives that conforms to ASTM C926 is designed as a replacement to job-site mixed scratch and brown base coats. ASTM C897 or ASTM C144 sand is added at job site.</p>	80 lbs	35/pallet	At 3/8": 100-140 At 3/4": 50-70
	<p><b>Fiber 47 Fastwall Scratch &amp; Brown Sanded</b></p> <p>A factory controlled high-quality blend of portland cement, lime, fibers, proprietary additives and ASTM C144 sand that conforms to ASTM C926 is designed as a replacement to job-site mixed scratch and brown base coats.</p>	80 lbs	35/pallet	At 3/8": 20-24 At 3/4": 10-12
	<p><b>Poly-Bond</b></p> <p>Poly-Bond is for use as a basecoat and adhesive for expanded polystyrene foam shapes. These shapes are typically used as exterior decorative trim such as pop-outs, plant-ons, cornices and quoins. Available in 2 textures: Coarse (for maximum keying strength) and Fine (for complex architectural details).</p>	50 lbs	56/pallet	50-70
	<p><b>Parex USA Stucco Level Coat</b></p> <p>Stucco Level Coat is a surface leveler and mesh adhesive for use in Parex USA Krak-Shield assemblies. Bonds to stucco brown coat. Can be applied in a thin layer. Applied without the addition of cement. Mixed on site with water only. Excellent workability.</p>	50 lbs	56/pallet	65
	<p><b>Fastwall Accel-Cure</b></p> <p>Excellent as a base for smooth finishes. No moist curing required. High PSI. High tensile strength. Under normal conditions, ready to accept finish after 24 hours. Fastwall Accel-Cure is a factory controlled high-quality blend of portland cement, lime, fibers and proprietary additives that conforms to ASTM C926. ASTM C897 or ASTM C144 sand is added at the job-site. Can be installed up to 1/2 in. (12.7mm) in one application.</p>	80 lbs	35/pallet	Base: 55-70 Brown coat: 70-90

STUCCO BASECOATS (continued)		Size	Pack	Coverage (ft <sup>2</sup> )
 <p><b>Parex USA Sandable Basecoat</b> A 100% Acrylic sandable basecoat that comes as a white base. It enhances the appearance and uniformity of smooth finishes. It can be easily recoated with Parex USA Allegro II. Ideal over EIFS basecoats, stucco basecoats, stucco finishes, and interior drywall.</p>	1 gal	NA	40-50	
	5 gal	56/pallet	200-250	
EIFS ADHESIVES & BASECOATS		Size	Pack	Coverage (ft <sup>2</sup> )
 <p><b>Insul-Bond Dry</b> A basecoat for LaHabra EIFS. Adhesive to laminate EPS to listed substrates. Applied without the addition of cement. Mixed on site with water. Excellent workability.</p>	50 lbs	56/pallet	As an Adhesive: 5/16" notched trowel: 130-140 As an Adhesive: 5/8" notched trowel: 90-100 As an Adhesive: 1/2" notched trowel: 110-120 As a Basecoat w/ standard mesh: 75-95 Double Layer Basecoat w/ ultra high impact mesh: 35-55	
 <p><b>Insul-Bond Wet</b> A basecoat for LaHabra EIFS. Adhesive to laminate EPS to listed substrates. Used in a 50% acrylic paste to 50% portland cement by weight ratio. Requires the addition of portland cement.</p>	5 gal	36/pallet	As an Adhesive: 5/16" notched trowel: 220-250 As an Adhesive: 5/8" notched trowel: 170-190 As an Adhesive: 1/2" notched trowel: 215-240 As a Basecoat w/ standard mesh: 180-210 Double Layer Basecoat w/ ultra high impact mesh: 150-190	
 <p><b>Parex USA 30# Cement</b> 30 lbs. bag portland cement. Used in conjunction with LaHabra Insul-Bond Wet.</p>	30 lbs	48/pallet	NA	
 <p><b>Parex USA Accel-Pak</b> Rapid set admix for any Parex USA polymer modified EIFS Basecoat &amp; Adhesive to reduce set time for Winter weather or quick EIFS patch and repair work.</p>	1 lb	30/case	NA	
 <p><b>EIFS Sheathing &amp; Adhesive</b> An adhesive to laminate EPS to listed substrates. A 100% acrylic polymer base. Ready to use, applied without the addition of cement. Exceptional workability.</p>	5 gal	36/pallet	5/16" notched trowel: 270-290 3/16" notched trowel: 320-350	



EIFS ADHESIVES & BASECOATS (continued)		Size	Pack	Coverage (ft <sup>2</sup> )
	<p><b>Parex USA Quick Base EIFS Base &amp; Adhesive</b> A base coat and adhesive for Parex USA EIFS. Single component 100% acrylic polymer base. Ready to use, applied without the addition of cement. First EIFS base coat &amp; adhesive to be packaged in a box for easier waste management on the jobsite and less impact on landfills.</p>	50 lbs	48/pallet	<p>As an Adhesive: 5/16" notched trowel: 161-192 As an Adhesive: 3/16" notched trowel: 246-269 As a Basecoat w/ standard mesh: 77-92 Double Layer Basecoat w/ ultra high impact mesh: 42-58</p>
BONDING AGENTS & ADMIXTURES (PAREX USA)		Size	Pack	Coverage (ft <sup>2</sup> )
	<p><b>Parex USA Adacryl Admix &amp; Bonder</b> 100% acrylic emulsion designed for use with for portland cement based products. High-performance acrylic polymer bonding agent. Admixture in portland cement based mixes.</p>	5 gal	36/pallet	1000-1500
		1 gal	6/case	200-300
		1 qt	NA	50-75
MESH (PAREX USA)		Size	Pack	Coverage (ft <sup>2</sup> )
	<p><b>G343.8 Stucco Mesh</b> 4.5 oz. fiberglass 38 in mesh. Is highly flexible for full walls or details. Is alkali resistant. Is used for reinforcement of stucco assemblies. Not for use on Exterior Insulation and Finish Systems (EIFS). Mesh is green.</p>	38" x 150'	4/case	475
	<p><b>G355 Standard Mesh - 4.5 oz.</b> 4.5 oz. fiberglass 38 in. wide mesh. Is highly flexible for full walls or details. Is alkali resistant. Standard reinforcement of Parex USA EIFS walls for impact resistance and details. Also used in Parex USA Krak-Shield.</p>	38" x 150'	4/case	475
	<p><b>G355.48 Long Standard Mesh - 4.5 oz.</b> 4.5 oz. fiberglass 48 in. wide mesh. Is highly flexible for full walls or details. Is alkali resistant. Standard reinforcement of Parex USA EIFS walls for impact resistance and details. Also used in Parex USA Krak-Shield.</p>	48" x 150'	4/case	600
	<p><b>G358.20 Ultra High Impact Mesh - 20 oz.</b> 20 oz. fiberglass 38 in. wide mesh. Is an ultra high-strength mesh used to enhance impact and abuse resistance. Is alkali resistant. Use with Parex USA EIFS to achieve EIMA's ultra-high impact strength classification. 355 Standard Mesh is required in combination with 358.20 Ultra High Impact Mesh.</p>	38" x 75'	2/case	237

MESH (PAREX USA) (continued)		Size	Pack	Coverage (ft <sup>2</sup> )
	<p><b>G358.10 Intermediate Mesh - 12 oz.</b> 12 oz. fiberglass 38 in. (96.5 cm) wide mesh. Is an intermediate strength mesh used to enhance impact and abuse resistance. Is alkali resistant. Use with Parex USA EIFS to achieve EIMA's medium impact strength classification. Can be used in combination with 355 Standard Mesh and 356 Short Detail Mesh. May be used in Parex USA Krak-Shield assembly.</p>	38" x 75'	4/case	237
	<p><b>G357 Corner Mesh - 7.2 oz.</b> 7.2 oz. fiberglass 9.5 in. (24 cm) wide mesh. Is a heavy duty mesh designed to fold uniformly around corners to reinforce, enhance impact and abuse resistance. Is alkali resistant. Used in combination with 355 Standard Mesh, 356 Short Detail Mesh, 358.10 Intermediate Mesh, 358.14 High Impact Mesh or 358.20 Ultra High Impact Mesh. May be used in Parex USA Krak-Shield assembly.</p>	9.5" x 164'	4/case	130
	<p><b>G356 Short Detail Mesh - 4.5 oz.</b> 4.5 oz. fiberglass 9.5 in. (24 cm) wide mesh. Is highly flexible for use on details. Is alkali resistant. Ideal for use in back wrapping, corners, reveals and trim. May be used in combination with 355, 358.6 &amp; 358.10 meshes in Parex USA Krak-Shield assemblies.</p>	9.5" x 150'	16/case	119
	<p><b>G352 Adhesive Mesh - 4.5 oz.</b> 4.5 oz. fiberglass mesh. Self Adhesive, facilitates the wrapping of complex contours. Highly flexible for details. Is alkali resistant. Used for backwrapping, corners, reveals and trims. NOTE: Complex architectural details only, not for use on full walls.</p>	19" x 150'	8/case	237
WEATHERTECH (PAREX USA)		Size	Pack	Coverage (ft <sup>2</sup> )
	<p><b>WeatherSeal Spray &amp; Roll-On</b> A 100% Acrylic co-polymer fast drying vapor retarder, elastomeric water-proof and air barrier coating which can be either rolled, brushed, or spray applied. Is designed for use as vapor retarder behind exterior claddings. Is extremely flexible: can bridge cracks and accommodate small movements up to 1/32 in. (0.8 mm). Bridges 1/4 in. (6 mm) gaps at sheathing board joints with Parex USA 396 Sheathing Tape embedded.</p>	5 gal	36/pallet	400-500
	<p><b>WeatherSeal Trowel-On with Gauging</b> A 100% acrylic based, trowelable water-resistive barrier membrane. Designed for use as water-resistive barrier behind exterior claddings. Extremely flexible: can bridge existing hairline cracks and accommodate small movements.</p>	5 gal	36/pallet	150-190
	<p><b>WeatherSeal Trowel-On without Gauging</b> A 100% acrylic based, trowelable water-resistive barrier membrane. Designed for use as water-resistive barrier behind exterior claddings. Extremely flexible: can bridge existing hairline cracks and accommodate small movements.</p>	5 gal	36/pallet	140-160

WEATHERTECH (PAREX USA)		Size	Pack	Coverage (ft <sup>2</sup> )
	<p><b>WeatherDry</b> An acrylic co-polymer based, waterproofing base coat. For use with acrylic and elastomeric finishes. Requires the addition of portland cement.</p>	5 gal	36/pallet	As an Adhesive: 80-100 As a Basecoat w/ standard Mesh: 90-110
	<p><b>WeatherSeal BG</b> A single-component, non-fibrated, asphalt modified, neoprene waterproofing membrane which can be either troweled, rolled, brushed, or spray applied. Designed to provide high-performance below grade protection from positive side water pressure. Allows low levels of moisture vapor to escape to prevent blistering and delamination of the applied membrane while prohibiting infiltration of moisture through foundation walls, footings, retaining walls, planter boxes and between slab. Solvent free formulation incorporate anti-microbial additive to prevent mold and mildew growth.</p>	5 gal	36/pallet	250-260
	<p><b>WeatherBlock Spray &amp; Roll-On</b> A 100% acrylic elastomeric waterproof membrane and air barrier which can be either rolled, brushed, or spray applied. Extremely flexible: can bridge cracks and accommodate small movements up to 1/32 in. (.8mm). Designed for use as water-resistive barrier behind LaHabra EIFS or stucco. Bridges 1/4 in. (6mm) gaps at sheathing board joints with 396 Sheathing Tape embedded.</p>	5 gal	36/pallet	350-400
WATERMASTER COMPONENTS (PAREX USA)		Size	Pack	Coverage (ft <sup>2</sup> )
	<p><b>Sheathing Tape</b> Non-woven fabric used to tape the joints of the sheathing boards to which a Parex liquid water-resistive barrier is applied.</p>	4" x 500'	NA	166
		6" x 500'	NA	250
		9" x 500'	NA	375
	<p><b>369 DrainEdge Weep Strip</b> Speeds and simplifies application of the WaterMaster systems and assemblies. Eliminates need for pre-wrapping or rasping the back of boards at terminations. Eliminates the need for mineral wool and track at terminations.</p>	7" x 200'	NA	116
	<p><b>Flashing Membrane</b> Self-sealing rubberized asphalt membrane that functions as a moisture and air barrier. It is 30 mils thick and black in color. Apply to various substrates: wood, metal, gypsum sheathing and to house wrap and other weather resistive barriers. This membrane is unique: it is faced with a non-woven, integrally bonded fabric that enables adhesion of Parex USA adhesives. It functions as a seal and flashing at sills of rough openings, deck framing, etc., interfacing with the building substrate and other weather resistive barriers.</p>	6" x 100'	8/case	50

Parex USA, Inc.  
4125 E. La Palma Ave., Suite 250  
Anaheim, CA 92807  
(866) 516-0061 Tech Support: (800) 226-2424



PAREXUSA  
SUSTAINABILITY

EIFS SOLUTIONS • STUCCO ASSEMBLIES • TILE AND STONE SYSTEMS **PAREXUSA** ENVISION IT ALL

© 2013, Parex USA, Inc. • LH PLS BR 1113